

J904B BASE MOUNTED JIB CRANE GENERAL ARRANGEMENT
NOTE: 1. BASE PLATE O.D. 6" LARGER THAN BOLT CIRCLE.

\*2. MODEL NO. 300 (HEAVY), 360 & 420 HAS SHIMS
ON TOP OF HEAD ASSY. UNDER BOOM.

\*\*3. "L" DIM. FOR MODEL 300L IS 7'-0".

|   | MODEL NO. | DIMENSIONS |            |            |         | ANCHOR BOLTS |          |           |        |
|---|-----------|------------|------------|------------|---------|--------------|----------|-----------|--------|
|   | J-904B-   | F1         | F2         | Z          | L       | PATT NO.     | B.C. DIA | BOLT DIA. | Р      |
|   | 080       | 1'-0 1/8"  | 1'-1 1/2"  | 1'-1 5/8"  | 4'-0"   | 6            | 24"      | 1"        | 4 3/4" |
|   | 120       | 1'-3"      | 1'-5 1/4"  | 1'-5 1/8"  | 4'-6"   | 6            | 30"      | 1 1/4"    | 5 1/2" |
|   | 140       | 1'-5"      | 1'-7 1/2"  | 1'-7"      | 4'-6"   | 6            | 36"      | 1 1/4"    | 5 1/2" |
|   | 160       | 1'-4 3/8"  | 1'-7 3/4"  | 1'-7 3/4"  | 5'-0"   | 12           | 42"      | 1 1/4"    | 5 1/2" |
| X | 180       | 1'-6 3/8"  | 1'-9 1/2"  | 1'-9 3/4"  | 5'-0"   | 12           | 48"      | 1 1/4"    | 5 1/2" |
|   | 200       | 1'-8 3/8"  | 1'-11 3/4" | 1'-10 3/4" | 5'-0"   | 12           | 54"      | 1 1/4"    | 5 1/2" |
|   | 240       | 1'-11 1/8" | 2'-3 1/4"  | 2'-1 1/8"  | 6'-5"   | 12           | 60"      | 1 1/4"    | 5 1/2" |
|   | 300H **   | 2'-2"      | 2'-7 1/2"  | 2'-7"      | 8'-0"   | 12           | 66"      | 1 1/4"    | 5 1/2" |
|   | 360       | 2'-5"      | 2'-11 3/4" | 2'-10 3/4" | 8'-0"   | 6            | 72"      | 2 1/2"    | 8"     |
|   | 420       | 3'-0"      | 3'-6 7/8"  | 3'-3"      | 10'-10" | 6            | 78"      | 3"        | 9"     |

REINFORCING RODS

5/8" DIA TOP 3/4" DIA BOTTOM ON APPROX 12" CTRS. BOTH WAYS.

ANCHOR BOLTS

BY OTHERS

CONCRETE -

FOUNDATION

BY OTHERS

CATALOG MODEL: 4B0741

MODEL NO.: J-904-180-W18B

CAPACITY: 2 TON (4000#)

WEIGHT: 3585

A 20'-0"

B 12'-0"

C 13'-6 1/8"

D W18X55 - D 18 1/8", FW 7 1/2"

E 4'-0"

W 8'-0"

SALES NO: CUST. ORDER NO:

## RECOMMENDED INSTALLATION PROCEDURE

SEE BULLETIN I.I. J-904B INSTALLATION INSTRUCTIONS FOR BASE MOUNTED PILLAR JIB CRANE MODEL J-904B.

## RECOMMENDED FOUNDATION CONCRETE

JIB CRANE FOUNDATION REQUIREMENTS ARE BASED ON A SOIL PRESSURE OF 2500 LBS. PER SQUARE FOOT. 3000 LBS. P.S.I. (PER SQ. INCH) COMPRESSIVE CONCRETE (5 BAG MIX-ONE YARD OF CONCRETE).

ABELL-HOWE CRANES, ASSUMES NO RESPONSIBILITY FOR LOADING IMPOSED ON BUILDING STRUCTURE OR FOOTINGS BY THIS EQUIPMENT. WE SUGGEST THIS BE CHECKED BY A LICENSED STRUCTURAL ENGINEER AND ANY NECESSARY PERMITS BE SECURED.

INSTALLATION DRAWING 360° BASE MOUNTED

PILLAR JIB CRANE MODEL J-904B

ABELL-HOWE CRANES

DIVISION OF CRANE, EQUIPMENT & SERVICE, INC.

10321 WERCH DR. UNIT 100, WOODRIDGE, ILLINOIS 60517

SCALE: NONE CHECKED BY:

DRAWN BY: RKN APPROVED BY:

DATE: 9/19/2006

DWG NO.: A3-J904B

SHEET NO. 1 OF 1