Short handle puller

- Easy one-hand operation
- Lever pull range is 45 to 62 pounds to lift full load
- Handle that rotates 360°, making it easy to operate in any position and in small spaces
- Tough yet lightweight aluminum construction and powder coat finish
- Hoistaloy hardened steel load chain for strength, long wear life and flexibility

- Free chaining for fast, easy attachment to load
- Forged upper and lower hooks with latches
- Simple construction with fewer parts for ease of maintenance
- Optional Load Limiter device protects against overload
- · Lifetime warranty
- · Made in U.S.A.



Rated capacity* (tons)	Product code	Standard lift (ft.)	Pull to lift full loads (lbs.)	Minimum distance between hooks (in.)	Lever length (in.)	Reeving	Hook throat openings (in.)	Approx. shipping weight (lbs.)
3/4	7300P	5	45	12 ¹ / ₄	12	1	1 ¹ /32	16
11/2	7320P	5	55	143/4	16 ³ / ₄	1	1 ¹ /8	27
3	7330P	5	62	17 ⁵ /8	163/4	2	13/16	40

Specifications -Short handle puller without chain

Rated capacity* (tons)	Product code	Approx. shipping weight (lbs.)
3/4	7301P	12
11/2	7321P	21
3	7331P	28



Optional Load Limiter

Optional kits

		Product code	Approx. shipping weight (lbs.)	Rated capacity* (tons)
Load Limiter		7310P	1	3/4
Load Limiter		7311P	2	1 ¹ /2-3
Anchor Sling		7309P	2	3/4
Anchor oning		7312P	3	1 ¹ /2
	upper	1001	2	3/4
		1003	2	1 ¹ /2
Latchlok Hook		1004	3	3
Laterilok 1100k	lower	1001	2	3/4
		1003	2	11/2
		1005	3	3



Optional upper Latchlok Hook 3/4 - 11/2 ton



Optional upper Latchlok Hook 3 ton



Optional anchor sling