
Lifting Solutions for Light Duty Applications



COFFING EMC & EMW Models - Compact chain and wire rope hoists designed for a variety of light duty applications. These models feature thermally protected motors.

- Capacities & Lift Rated loads 300 and 500 pounds. 10-foot lift with 6-foot push button cord standard.
- **Voltages** 115V, single phase motors only.
- **Suspension** Swivel top and bottom hooks with safety latches standard.
- **Power Cord** Provided with grounded 3-prong plug for easy installation in any standard 115V outlet.
- Aluminum Housing Lightweight and compact to provide strength and portability. Weighs less than 25 lb.
- **Limit Switches** Upper and lower limit switches on chain models and upper paddle limit switch on wire rope model regulates load travel.
- **Electromagnetic Brake** Quick acting for positive load control.
- **Thermal Motor Protection** Standard to prevent overheating.
- **Light Duty Operation** Rated for intermittent duty applications (10-minute run time per hour maximum).
- Accessories LCC-05 chain container (shown) available for EMC models.
- **UL Listed**
- Lifetime Warranty

Coffing EMC & EMW Models-Chain & Wire rope Hoist designed for a variety of light duty applications:

Machine Shops

Automotive Aftermarket

General Maintenance

S P E C I F I C A T I O N S

EMC & EMW Models

C	Capacity (Lb.)	Model Number	No. of Chains	Standard Lift (Ft.)	Motor HP	Lift Speed (FPM)	Headroom (In.)	Hous H	ing Dimensi W	ons (In.) L	Net Wt. (Lb.)
	300	EMC-300B	1	10	1/6	16	141/2	43/8	63/8	141/4	21
	500	EMC-500B	2	10	1/6	8	16	43/8	63/8	14 ¹ / ₄	24
	500	EMW-500B	2-part wire rope	10	1/6	16	133/4	43/8	63/8	14 ¹ / ₄	19

High Performance Lifting

Country Club Road • PO Box 779 Wadesboro, NC 28170 USA

Phone:

 Do not use to lift people or loads over people. Use only alloy chain and attachments for overhead lifting. Read and follow all instructions.

To Avoid Injury:

Overloading and Improper Use Can Result In Injury

Do not exceed working load limit, load rating, or capacity.

(800) 477-5003 (704) 694-2156 FAX: (800) 374-6853 (704) 694-6829

CB-26 Printed in USA © 2004 Coffing Hoists

www.coffinghoists.com • e-mail: coffing@cmworks.com