


# ROSS CHAIN HOISTS

## Model – HSZ-C

### 1/2 to 10 Ton Hand Chain Hoists

- Standard lifts in 10, 15 and 20 feet
- Special lifts available upon request
- Hand Chain drop is 2-feet less than lift
- Forged upper and lower hooks with latches
- Lubricated bearings and bushings, and heat-treated two-step spur gears ensures smooth and efficient operation with minimal effort.
- Metric rated, providing 10% greater lifting capacity than most other hoists
- Mechanical ratchet disc load brake engages instantly for precise load holding and positioning.
- Meets ANSI B30.16 Specifications
- CE and GS Certified
- Individual serial numbers stamped on hoists
- All hoists tested at 125% of rated load prior to shipment
- Individual Load Test Certificates provided with each hoist
- 1 Year Warranty against any defects in materials or workmanship

The Ross HSZ-C hand chain hoists are manufactured with high quality light-weight stamped steel housings. Compact gear housing design provides for low headroom applications



Part Number	Capacity* Lbs./Tons	Lift (ft.)**	Strands of Load Chain	Min. (in.) Headroom	Hand effort to lift full working load (lbs.)	Shipping Weight (lbs.)
RH0.510	1100 / 1/2	10	1	12 1/4	59	20
RH0.515	1100 / 1/2	15	1	12 1/4	59	25
RH0.520	1100 / 1/2	20	1	12 1/4	59	29
RH1.010	2200 / 1	10	1	14 1/8	65	27
RH1.015	2200 / 1	15	1	14 1/8	65	32
RH1.010	2200 / 1	20	1	14 1/8	65	38
RH2.010	4400 / 2	10	1	16 7/8	78	47
RH2.015	4400 / 2	15	1	16 7/8	78	56
RH2.020	4400 / 2	20	1	16 7/8	78	63
RH3.010	6600 / 3	10	2	19 1/4	89	48
RH3.020	6600 / 3	20	2	19 1/4	89	59
RH5.010	11000 / 5	10	2	26 5/8	90	88
RH5.020	11000 / 5	20	2	26 5/8	90	119
RH10.10	22000 / 10	10	4	34 5/8	90	155
RH10.20	22000 / 10	20	4	34 5/8	90	210

\* Hoists are metric rated (Metric Ton) \*\* Standard Lifts are shown. Other lifts available upon request.

