

ROSS LEVER HOISTS

Model – HSH-A 3/4 to 6 Ton Lever Hoist

The Ross HSH-A double lever hoists are manufactured with high quality impact resistant all steel frame, gear case and cover. This proven design can withstand years of heavy-duty use.



- **Standard lifts in 5, 10, 15 and 20 feet**
- **Special lifts available upon request**
- **Forged upper and lower hooks with latches**
- **Lightweight stamped steel design**
- **Metric rated, providing 10% greater lifting capability than most other lever hoists**
- **Dual pawls for added safety**
- **Rubber handle for ease of use**
- **Free wheeling mechanism allows for quick and easy take-up and positioning of hook**
- **Steel, heavy-duty free wheeling knob**
- **Meets ANSI B30.21 Specifications**
- **CE and GS Certified**
- **Individual serial numbers stamped on hoists**
- **All hoists tested at 125% of rated load prior to shipment**
- **Individual Load Test Certificates provided with each hoist**
- **1 Year Warranty against any defects in materials or workmanship**

Part Number	Capacity* Lbs./Tons	Lift (ft.)**	Strands of Load Chain	Min. Distance Between Hooks (in.)	Handle Length (in.)	Average Handle Effort	Shipping Weight (lbs.)
RL0.755	1650 / 3/4	05	1	12 5/8	11	46	15
RL0.7510	1650 / 3/4	10	1	12 5/8	11	46	18
RL0.7515	1650 / 3/4	15	1	12 5/8	11	46	20
RL0.7520	1650 / 3/4	20	1	12 5/8	11	46	23
RL1.55	3300 / 1 1/2	05	1	14 1/8	16 1/8	53	23
RL1.510	3300 / 1 1/2	10	1	14 1/8	16 1/8	53	28
RL1.515	3300 / 1 1/2	15	1	14 1/8	16 1/8	53	33
RL1.520	3300 / 1 1/2	20	1	14 1/8	16 1/8	53	37
RL3.05	6600 / 3	05	1	8 1/2	16 1/8	71	40
RL3.010	6600 / 3	10	1	8 1/2	16 1/8	71	47
RL3.015	6600 / 3	15	1	8 1/2	16 1/8	71	56
RL3.020	6600 / 3	20	1	8 1/2	16 1/8	71	64
RL6.05	13200 / 6	05	2	22 1/4	16 1/8	58	58
RL6.010	13200 / 6	10	2	22 1/4	16 1/8	73	73
RL6.015	13200 / 6	15	2	22 1/4	16 1/8	88	88
RL6.020	13200 / 6	20	2	22 1/4	16 1/8	103	103

