



CLAMPS & TROLLEYS

Beam Clamp Rated loads from 1 – 10 Ton



- Special clamp design distributes weight away from flange edges.
- Threaded screw allows beam clamp to fit securely on a wide range of flange widths and beam sizes.
- Low headroom provided by built in suspension bar
- GS and CE certified
- Meets or exceeds ANS B30.16 Specifications
- Tested at 125% of rated load prior to shipment
- Individual Serial Numbers stamped into each Beam Clamp
- Individual Load Test Certificates provided with each Beam Clamp
- 1 Year warranty against any defects in material or workmanship




Part Number	Capacity Lbs./Tons	I-Beam Flange Width (in.)	Strands of Load Chain
RBC1.0	2200 / 1	3-9	10
RBC2.0	4400 / 2	3-9	12
RBC3.0	6600 / 3	3.2-12.6	23
RBC5.0	11000 / 5	3.2-12.6	25
RBC10.0	22000 / 10	3.5-12.6	35

Plain Trolley Rated loads from 1/2 – 10 Ton



- Metric rated
- Dual Tread Wheels – Cast Iron wheels fit any flat beam or tapered beam within the ranges specified.
- Wheels include permanently lubricated and shielded bearings for long life and low maintenance
- GS and CE certified
- 1 Year warranty against any defects in material or workmanship
- Meets or exceeds ANSI B30.16 Specifications
- Tested at 125% of rated load prior to shipment
- Individual Serial Numbers stamped into each trolley
- Individual Load Test Certificates provided with each Trolley



Part Number	Capacity* Lbs./Tons	Standard Beam Height (in.)	I-Beam Flange Width (in.)	Wheel Tread Diameter	Shipping Weight (lbs.)
RT0.5	1100 / 1/2	4-10	2.55-5.51	2 3/4	17
RT1.0	2200 / 1	5-12	2.55-5.51	2 3/4	27
RT2.0	4400 / 2	6-18	3.46-5.75	3 1/3	49
RT3.0	6600 / 3	8-20	4.33-6.0	3 5/7	67
RT5.0	11000 / 5	10-24	4.57-6.69	4 1/4	122
RT10.0	22000 / 10	10-24	4.92-8.0	5 1/2	208