

Single-Path & Twin-Path® High Performance Slings with Check-Fast® System



Check-Fast® Inspection System

Now available in Polyester or K-Spec® Single-Path and Twin-Path® Roundslings



Single-Path Extra Covermax® with Check-Fast® Inspection

Single-Path K-Spec® Slings Stock No.	Rated Capacities (Lbs.) 5:1 DF					Approximate Weight (Lbs. per Ft.) (Bearing-Bearing)	Nominal Body Width (Inches)
	Vertical	Choker	Vertical Basket	Basket Hitches			
			90°	60°	45°		
SPXCF 500	5,000	4,000	10,000	8,660	7,070	.34	2.5"
SPXCF 1000	10,000	8,000	20,000	17,320	14,140	.38	2.5"
SPXCF 1500	15,000	12,000	30,000	25,980	21,210	.44	2.5"
SPXCF 2000	20,000	16,000	40,000	34,640	28,280	.52	2.5"
SPXCF 2500	25,000	20,000	50,000	43,300	35,350	.59	3"
SPXCF 3000	30,000	24,000	60,000	51,960	42,420	.65	3"
SPXCF 4000	40,000	32,000	80,000	69,280	56,560	.85	3"
SPXCF 5000	50,000	40,000	100,000	86,600	70,700	.98	4"
SPXCF 6000	60,000	48,000	120,000	103,920	84,840	1.11	4"
SPXCF 7000	70,000	56,000	140,000	121,240	98,980	1.24	4"
SPXCF 8500	85,000	68,000	170,000	147,220	120,190	1.63	5"
SPXCF 10000	100,000	80,000	200,000	173,200	141,400	1.81	5"

DO NOT EXCEED RATED CAPACITY

DO NOT EXCEED RATED CAPACITY

Twin-Path® Extra Covermax® with Check-Fast® Inspection

PLEASE NOTE: Capacities shown include both paths and are for one complete sling. Sling ratings based on fittings of equal or greater capacity. Conforms to ANSI/ASME B30.9 chapter 6, NAVFAC P-307 section 14.6.4.3, and the Cordage Institute Roundslings Standard.

Twin-Path® K-Spec® Slings Stock No.	Rated Capacities (Lbs.) 5:1 DF					Approximate Weight (Lbs. per Ft.) (Bearing-Bearing)	Nominal Body Width (Inches)
	Vertical	Choker	Vertical Basket	Basket Hitches			
			90°	60°	45°		
TPXCF 1000	10,000	8,000	20,000	17,320	14,140	.40	1.5 - 3"
TPXCF 1500	15,000	12,000	30,000	25,980	21,210	.45	1.5 - 3"
TPXCF 2000	20,000	16,000	40,000	34,640	28,280	.51	1.5 - 3"
TPXCF 2500	25,000	20,000	50,000	43,300	35,350	.57	1.5 - 3"
TPXCF 3000	30,000	24,000	60,000	51,960	42,420	.71	2.0 - 4"
TPXCF 4000	40,000	32,000	80,000	69,280	56,560	.83	2.0 - 4"
TPXCF 5000	50,000	40,000	100,000	86,600	70,700	1.14	2.5 - 5"
TPXCF 6000	60,000	48,000	120,000	103,920	84,840	1.27	2.5 - 5"
TPXCF 7000	70,000	56,000	140,000	121,240	98,980	1.39	2.5 - 5"
TPXCF 8500	85,000	68,000	170,000	147,220	120,190	1.65	3.0 - 6"
TPXCF 10000	100,000	80,000	200,000	173,200	141,400	1.84	3.0 - 6"
TPXCF 12500	125,000	100,000	250,000	216,500	176,750	2.35	4.0 - 8"
TPXCF 15000	150,000	120,000	300,000	259,800	212,100	2.66	4.0 - 8"
TPXCF 17500	175,000	140,000	350,000	303,100	247,450	3.14	5.0 - 10"
TPXCF 20000	200,000	160,000	400,000	346,400	282,800	3.45	5.0 - 10"
TPXCF 25000	250,000	200,000	500,000	433,000	353,500	4.07	5.0 - 10"
TPXCF 27500	275,000	220,000	550,000	476,300	388,850	4.61	6.0 - 12"
TPXCF 30000	300,000	240,000	600,000	519,600	424,200	4.92	6.0 - 12"
TPXCF 40000	400,000	320,000	800,000	692,800	565,600	6.54	7.0 - 14"
TPXCF 50000	500,000	400,000	1,000,000	866,000	707,000	8.15	8.0 - 16"

DO NOT EXCEED RATED CAPACITY

DO NOT EXCEED RATED CAPACITY



Sling can fail if damaged, misused or overloaded. Inspect before use. Damaged sling shall not be used. Use only if trained. Do not exceed rated capacity. Protect sling from being cut by load edges, corners, protrusions and abrasive surfaces. Avoid exposure to acid, alkali and temperature over 180°F. DEATH or INJURY can occur from improper use or maintenance.

